

Software updates

Updating software of the Nagra VI is very straightforward, although a simple procedure needs to be strictly followed.

To update the version of internal software, use a blank compact flash card or USB key of minimum 256 MB. (We suggest reformat the media before starting, although this is not obligatory)

1. Copy the new software file named "NVI_xxx_yyy.nbu" in to the root directory of the CF card, from our web site www.nagraaudio.com under the Pro\Support\Nagra VI selection. The four xxx characters indicate the hardware version for the software and the three characters "yyy" in the file name correspond to the software version of the new file.

2. Switch ON the Nagra VI in the STOP position using the main function selector. When booting is completed press "ESC" until you see the standby display on the screen (NOT the Date / Time setting screen).

3. Insert the CF card or USB key containing the update file. The machine will automatically recognize the new file on the card and will display the update message on the main display requesting:

"Valid version xxx available"
"Press Right to update or ESC to cancel"

4. Press the Right key and the update will be performed automatically and this process takes about 15 seconds. Do NOT remove the CF card while the update is in progress.

5. Once completed you will be prompted to REMOVE the CF card and switch the NAGRA VI OFF. Upon restart the new software version will be installed.

IMPORTANT: CF cards with the "xxxx_xxx.nbu" file in the root directory cannot be used for recording until the card has been reformatted or the .nbu file erased.
If power is lost during the update process, the machine will use its internal recovery system and will ask for the update compact flash to be inserted at power up.

WARNING: Personal settings and template settings may be lost during this process, depending on the software modifications of the update.